

## ANYSTREAM® CLASSIC

### Showerheads GENERAL SPECIFICATION

Water conserving pressure compensating Autoflo® device reduces flow to 2.5 GPM/9.46LPM maximum, to meet existing ANSI A112.18.1/CSA B125.1/CSA B125.1 Standard. ½" N PT inlet.

#### □ S-2251

Polished chrome plated Anystream® showerhead. Brass ball swivel joint. Brass shank. Spray adjusting handle. 3-1/2" face. 8 Lexan deposit resisting plungers with 64 spray channels.

#### □ S-2252

Polished chrome plated Anystream® showerhead. Brass ball swivel joint. Brass shank. Spray adjusting peanut handle. 2-3/4" face. 6 Lexan deposit resisting plungers with 48 spray channels.

#### □ S-2253

Polished chrome plated Anystream® showerhead. Brass ball swivel joint. Chrome plated shank. Spray adjusting T-handle. 2-1/4" face. 4 Lexan deposit resisting plungers with 32 spray channels.

### OPTIONS

SUFFIX	DESCRIPTION
□ E2	2.0 GPM flow rate (S-2252 & S-2253 only)
□ E175	1.75 GPM flow rate (S-2253 only)
□ E15	1.5 GPM flow rate (S-2253 only)
□ PB	Polished brass finish (S-2251 & S-2252 only)
□ BP	Blister pack packaging (S-2252 & S-2253 only)
□ BPT	½" British pipe thread inlet
□ ORB	Oil rubbed bronze (S-2251 & S-2252 only)
□ PN	Polished nickel finish (S-2251 & S-2252 only)
□ BN	Brushed nickel finish (S-2251 & S-2252 only)



**S-2251**



**S-2252**



**S-2253**

This space for Architect/Engineer approval.

