

## ANYSTREAM® MASSAGE FIXED

### Showerheads

#### GENERAL SPECIFICATION

5 self-cleaning plunger nozzles resist scale build-up and provide 45 spray streams for a full body coverage pattern. Water conserving pressure compensating Autoflo® device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1/CSA B125.1 Standard. 1/2" NPT inlet.

**S-2007**



**S-2007**

Polished chrome plated Anystream® Napa showerhead. Swivel ball connector. Center core nozzle delivers pulsating massage jets. Combination spray available. Adjusting spray ring. Massage spray.

**S-3010**



**S-3010**

Polished chrome plated Anystream® Neo showerhead. 50 adjustable sprays. Swivel ball connector. Center core nozzle delivers pulsating massage jets. Combination spray available. Adjusting spray ring. Massage spray.

**S-3011**



**S-3011**

Polished chrome plated Anystream® Alexandria showerhead. Swivel ball connector. Center core nozzle delivers pulsating massage jets. Combination spray available. Adjusting spray ring. Massage spray.

**S-3014**

Polished chrome plated Anystream® Caspian showerhead. Swivel ball connector. Center core nozzle delivers pulsating massage jets. Combination spray available. Adjusting spray ring. Massage spray.

**S-3014**



**S-3020**

Polished chrome plated Anystream® Caspian showerhead. Swivel ball connector. Center core nozzle delivers pulsating massage jets. Combination spray available. Spray adjusting handle. 5/4" face.

**S-3020**



#### OPTIONS

SUFFIX	DESCRIPTION
<input type="checkbox"/> E2	2.0 GPM flow rate (not available on polished brass showerheads)
<input type="checkbox"/> PB	Polished brass (S-2007 only)
<input type="checkbox"/> BN	Brushed nickel finish

This space for Architect/Engineer approval.

