SPEAKMAN®

COMMANDER®

SC-3044-LD



SC-3046-LD



Widespread Lavatory Combinations

GENERAL SPECIFICATION 👆



Polished chrome plated Commander widespread lavatory faucet with 1/4 turn ceramic cartridges covered by a 25-year warranty. 8" fixed centers with rigid copper tee connection. Accommodates installations up to 1 ½" thick. Widespread faucet with 4-3/4" deep lavatory spout. Vandal-resistant water conserving flow control reduces flow to 2.2 gpm/8.4 lpm. Meets ASME A112.18.1/CSA B125.1 and NSF61.

4" Wrist Blade Handle Models

Vandal-resistant 4" wrist blade handles with color-coded indexes. □ SC-3034 Solid brass 1-1/4" pop-up drain

□ SC-3044 Strainer drain

□ SC-3044-LD No drain assembly

6" Wrist Blade Handle Models

Vandal-resistant 6" wrist blade handles with color-coded indexes.

□ SC-3036 Solid brass 1-1/4" pop-up drain

□ SC-3046 Strainer drain □ SC-3046-LD No drain assembly

OPTIONS

SUFFIX	DESCRIPTION
	0.5 gpm flow control, vandal-resistant
□ CA**	Low lead for CA AB1953 compliance
☐ GB	1.5 gpm flow control, vandal-resistant
☐ CWO	Cold water only (only available with FH option)
□ D75	Diamond 75 escutcheons
□ FH	Flex hose (3/8" x 3/8" compression)
□ LD	Less drain assembly (SC-3034 & SC-3036 only)
□ LF	2.2 gpm laminar flow control outlet
	Metal index for handles
	Satin chrome finish





^{**} The following options are not available with the "CA" option: HS (Hose & Spray), SO, TWI, VB6, VB8, ST, SW, & TMV.

www.speakmancompany.com


SPEAKMAN®

BOWL

Rough-Ins

SC-3044-LD 8" (203mm) 41/2" 2-1/4" DIA. 1 9/16" (114 mm) (40 mm) (57 mm) 4" (102 mm) 5/16" 1-1/8" DIA 11/16" DIA. 4-3/8" **DECK** (17 mm) 1-1/2" MAX (38.1 mm) SIDE VIEW OF GOOSENECK ASSEMBLY COLD INLET **HOT INLET** 1-3/8" 1-1/2" (38mm) (35mm) DIA DIAHÒLE HOLE-TYP 2" (51mm) MIN TO WALL 2" (51mm) MIN TO LEDGE

TOP VIEW OF ROUGHING IN HOLES
FOR LAVATORY



SC-3046-LD

