SPEAKMAN® SE-491-CV EYESAVER® EYE/FACE WASH

DESCRIPTION

Pedestal mounted emergency covered eye/face wash. Supplied with stainless steel bowl, stainless steel cover, stay-open full flow ball valve; activated by stainless steel push handle; twin spray heads with individual flow restrictors, and flip-off dust covers.

SPECIFICATIONS

Bowl: 300 Series Stainless Steel. Cover: 300 Series Stainless Steel. Spray Heads: (2) Yellow Plastic Spray Outlet, Sprayface, and Dust Cover. Valve: 1/2" NPT Female Brass, Chrome-Plated Activator: Stainless Steel Push Handle Inlet: 1/2" NPT Female Pipe: 1¹/₄" IPS Galvanized Steel Floor Flange: Brass Casting with (3) 17/32" diameter mounting holes on 9" diameter bolt circle spaced 120° apart Waste: 1¼" NPT Female. Finish: DuraJade™ Performance: 4.5 gpm @ 30 psi Compliance: ANSI Z358.1 Universal Emergency Sign Included

OPTION

🖵 HFO	Hand foot operation
G FLW	Flow switch
🖵 HS	Hand-held spray
G FPV	Anti-freeze protection valve
□ SPV	Anti-scald Protection valve
SSBV2	1/2" stainless steel valve

Job Name		
Location		
Architect/Engineer		
Sales Representative		
Wholesaler		
Date	Model #	

1⁷/₃₂" (29mm)

34" TO FLOOR

(864mm)

ł

5"

(127mm)

3³/₈" (86mm)

5½'

(140mm)

38¹⁹/₃₂" TO FLOOR

(980mm)

2¼" (57mm)

1 1/4" NPTF

WASTE

6" (152mm)

¢ ¢