## **SPEAKMAN®**

## SENTINEL MARK II®

SM-3410



# Anti-Scald Balanced Pressure Shower &

#### SM-3410

Sentinel Mark II concealed anti-scald balanced pressure shower with integral volume control/diverter and integral stops. Chrome plated brass wall plate with metal index. Chrome plated brass lever handle. Independent center sleeve allows up to 1" of rough-in variation. Adjustable temperature limit stop. Brass body. Pressure balancing and ceramic temperature regulating cartridge with built-in check valves. Can be installed back-to-back. Roughing-in template. S-2272-E2 showerhead with flow control device reduces flow to 2.0 gpm/7.57 lpm maximum to meet existing ASME A112.18.1/CSA B125.1 standard. S-2500 shower arm and wall flange. Four port valve with 1/2" female copper sweat inlets and shower outlet. 1/2" female NPT tub outlet. Furnished with 1/2" pipe plug. Meets ASSE 1016 & ASME 112.18.1/CSA B125.1.

#### **OPTIONS**

SUFFIX	DESCRIPTION
□ LH	Less showerhead
<b>□</b> 1	S-2251 showerhead
<b>□</b> 2	S-2252 showerhead
□ 2VR	S-2252 vandal-resistant showerhead
□ 3	S-2253 showerhead
<b>□</b> 6	S-2288 showerhead
□ 9	S-2292 showerhead

Contractor packs available upon request.





## **SPEAKMAN®**

### Rough-Ins

SM-3410

