# **SPEAKMAN®**

## SENTINEL PRO\*\*\*

SM-5420





### Anti-Scald Thermostatic/ Pressure Balanced Shower &

#### **GENERAL SPECIFICATION**

Speakman SentinelPro concealed anti-scald thermostatic/pressure balancing shower/bath valve combinations with integral volume control/diverter. Chrome plated brass wall plate. Chrome plated metal lever handle. Adjustable temperature limit stop (TLS). Factory set @ 110 F°. Brass body with integral spring check stops. Dual element thermostatic/pressure balancing cartridge. Can be installed back to back. Roughing-in template. S-2280 Anystream\* wall mounted showerhead with flow control device reduces flow to 2.5 gpm/9.46 lpm maximum. Vandal-resistant standard. Four port valve with 1/2" female copper sweat inlets and shower outlet. ½" NPT female tub outlet. Furnished with ½" pipe plug. Meets ASSE 1016 & ASME 112.18.1/CSA B125.1 standards.

Construction is Forged Brass Body and Glass Filled Resin Bonnet. Capacity is 4.0 GPM +/- .25 @ 45 psi (50/50 mix). Maximum Hot Water Supply Temperature is 185°F. Minimum Hot Water Supply Temperature is 5°F above set point. Maximum operating temperature is 125 psig. Valve Temperature Set Point is 110°F (Based on 115-120°F hot & 55 – 65°F Cold). Maximum Static Pressure is 125 psig. Minimum flow (for +/-3°F performance) meets 1016 to 1.5 gpm.

#### □ SM-5420

Anti-scald balanced pressure shower.

OPTIONS	
SUFFIX	DESCRIPTION
□AP	Anchor plate
□ BJ	Ball Joint (S-2280 showerhead only)
<b>1</b>	S-2251 showerhead
□ 2VR	S-2252 vandal-resistant showerhead
<b>4</b> 6	S-2288 showerhead
<b>9</b>	S-2292 showerhead



# **SPEAKMAN®**

### Rough-Ins

#### SM-5420

