

SHOWER ACCESSORIES

S-2310



VS-111



Shower Accessories

S-2310

Polished chrome plated brass thumb operated volume control. 1/2" NPT connections.

VS-111

Chrome plated brass shower diverter. 1/2" NPSF inlet. 1/2" NPSM outlet and side port outlet.

VS-113

Chrome plated plastic/brass 3-way shower diverter. 1/2"-14 NPSM threaded inlet and outlets. Swivel brass coupling nut. Handle turns 180° only. Three (3) operational diverter settings. 1/2" - 14 NPSM female supply inlet. Bottom and side port outlets. 1/2" - 14 NPSM male. No flow control inserted.

VS-115

Chrome plated brass supply ell with wall flange. 1/2" NPTF inlet. 1/2" NPSM outlet.

VS-117


Chrome plated brass in-line vacuum breaker. 1/2" NPSF inlet. 1/2" NPSM outlet. NOTE: Do not install VS-117 in concealed locations or where slight spillage under certain service conditions might cause water damage. Avoid continuous pressure applications (shut-off valve downstream of vacuum breaker).

VS-150

Chrome shower arm mount bracket to hold handheld shower. 1/2" -14 NPSM Threaded inlet and outlet. Easy seal and 2.5 GPM flow control inserted.

VS-152-6FT

Chrome 6' metal shower hose, 1/2"-14 NPSM female tangle free connectors.

VS-153-ADA 

24" combination slide bar and grab bar, stainless steel and chrome. Meets the ANSI standard 250 lbs. pull-test for grab bars and with ADA lever handle for adjusting slide bar.

OPTIONS

| SUFFIX | DESCRIPTION |
|-----------------------------|---|
| <input type="checkbox"/> BN | Brushed nickel (VS-111, VS-113, VS-150, VS-153-ADA) |
| <input type="checkbox"/> PB | Polished brass (VS-111, VS-113, VS-150, VS-153-ADA) |

VS-115



VS-113



VS-150-PC



VS-153-ADA



VS-117



VS-152



This space for Architect/Engineer approval.

