

ANYSTREAM® MASSAGE HAND-HELDS

GENERAL SPECIFICATION

5 self-cleaning plunger nozzles resist scale build-up and provide 45 spray streams for a full body coverage pattern. Water conserving pressure compensating Autoflo® device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1/CSA B125.1 Standard. 1/2" NPT inlet.

VS-2007



VS-2007

Polished chrome plated Anystream® Napa hand-held. Swivel ball connector. Center core nozzle delivers pulsating massage jets. Combination spray available. Adjusting spray ring. Massage spray.

VS-3010

Polished chrome plated Anystream® Neo hand-held. 50 adjustable sprays. Swivel ball connector. Center core nozzle delivers pulsating massage jets. Combination spray available. Adjusting spray ring. Massage spray.

VS-3011

Polished chrome plated Anystream® Alexandria hand-held. Swivel ball connector. Center core nozzle delivers pulsating massage jets. Combination spray available. Adjusting spray ring. Massage spray.

VS-3010



VS-3014

Polished chrome plated Anystream® Caspian hand-held. Swivel ball connector. Center core nozzle delivers pulsating massage jets. Combination spray available. Adjusting spray ring. Massage spray.

OPTIONS

SUFFIX	DESCRIPTION
<input type="checkbox"/> E2	2.0 GPM flow rate (not available with polished brass showerhead)
<input type="checkbox"/> BN	Brushed nickel finish
<input type="checkbox"/> PB	Polished brass finish (VS-2007 only)

VS-3011



VS-3014



This space for Architect/Engineer approval.

