400 Anchor Mill Rd., New Castle, DE 19720, USA
800-537-2107 | Fax: 800-977-2747
www.speakmancompany.com

SPEAKMAN®

ANYSTREAM® MASSAGE HAND-HELDS

VS-2007

VS-3010

GENERAL SPECIFICATION

5 self-cleaning plunger nozzles resist scale build-up and provide 45 spray streams for a full body coverage pattern. Water conserving pressure compensating Autoflo® device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1/CSA B125.1 Standard. 1/2" NPT inlet.

❑ VS-2007

Polished chrome plated Anystream® Napa hand-held. Swivel ball connector. Center core nozzle delivers pulsating massage jets. Combination spray available. Adjusting spray ring. Massage spray.

❑ VS-3010

Polished chrome plated Anystream® Neo hand-held. 50 adjustable sprays. Swivel ball connector. Center core nozzle delivers pulsating massage jets. Combination spray available. Adjusting spray ring. Massage spray.

❑ VS-3011

Polished chrome plated Anystream® Alexandria hand-held. Swivel ball connector. Center core nozzle delivers pulsating massage jets. Combination spray available. Adjusting spray ring. Massage spray.

❑ VS-3014

Polished chrome plated Anystream® Caspian hand-held. Swivel ball connector. Center core nozzle delivers pulsating massage jets. Combination spray available. Adjusting spray ring. Massage spray.

OPTIONS

SUFFIX	DESCRIPTION
❑ E2	2.0 GPM flow rate (not available with polished brass showerhead)
❑ BN	Brushed nickel finish
❑ PB	Polished brass finish (VS-2007 only)

VS-3011

VS-3014

This space for Architect/Engineer approval.

Anystream and Autoflo — Registered T.M. Speakman Company
© Copyright, Speakman Company, 2011