

ANYSTREAM® REFRESH HAND-HELDS

VS-3030



VS-3031



VS-3032



Hand-Held GENERAL SPECIFICATION

Flood, massage & needle spray outlets deliver invigorating sprays. 360° spray adjusting faceplate. Water conserving pressure compensating Autoflo® device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1/CSA B125.1 Standard. ½" NPT inlet.

VS-3030

Polished chrome plated Anystream® S-3030 hand shower. Includes a five foot long hose and swivel ball bracket for shower arm mounting. Spray adjusting, 4.5" face. Full spray and massage spray settings. Air injection face. Contemporary design.

VS-3031

Polished chrome plated Anystream® S-3031 hand shower. Includes a five foot long hose and swivel ball bracket for shower arm mounting. Spray adjusting, 3.75" face. Full spray, massage, aerated spray and pause settings. Air injection face. Traditional design.

VS-3032

Polished chrome plated Anystream® S-3032 hand shower. Includes a five foot long hose and swivel ball bracket for shower arm mounting. Spray adjusting, 4" face. Full spray, massage, and aerated spray settings. Air injection face. Modern design.

OPTIONS

SUFFIX	DESCRIPTION
<input type="checkbox"/> BN	Brushed nickel finish

This space for Architect/Engineer approval.

